



Size: 8.25x12.4











LIFT



PARKING



CCTV



24X7 SECURITY GUARD



WATER SUPPLY GENERATOR FOR COMMON AREA

Specifications

STRUCTURE

R.C.C. earthquake resistance structural with brick wall/fly ask as per design.

DOOR FRAMES

Door frame (Chaukhat) of Sal Wood with beating.

ENTRANCE DOOR

Entrance door shutters of 30 mm thick ISI mark one side Teak with Decorative beating/ designer skin venier.

OTHER DOORS

30 mm thick ISI mark factory made to shutter.

WINDOW

Fully glazed two track aluminum window with fly screen.

FLOORING

Designer Vitrified Flooring of ISI mark

KITCHEN

- (a) Flooring designer concept of ISI mark or equivalent tiles floor
- (b) Working platform : Black granite slab.
- (c) Dado 24" designer concept or equivalent tiles
- (d) Sink : Steel Sink
- (e) Water hot and cold for instant geyser point.
- (f) Aqua guard point in kitchen

DINING SPACE

One number ISI mark of equivalent white colour hand wash basin.

BATHROOM

- (a) Flooring Designer concept or equivalent tiles flooring.
- (b) Wall Designer Bathroom concept upto 7' height
- (c) Sanitary ware White glazed vitreous and wash basin of ISI mark.
- (d) Fitting Chromium plated C.P. fitting of ISI mark.
- (e) Water Hot & Cold in both toilets.

ELECTRICAL

- (a) All internal wiring in concealed conduits with copper wires
- (b) All electrical modular switches accessories of ISI marks.
- (c) Adequate lighting/power points sockets. outlets etc provided in all room

TV/CABLE & TELEPHONE SUPPLY

One TV point in two room and one telephone plug provided in

drawing room and master bedroom

INTERCOM

Intercom provided in all flats.

INTERNAL WALL

All internal walls shall be finished with white putty/Paris with primer.

EXTERNAL WALL FINISH

Finished with wall putty & weather coat paint

PARKING AREA

FLOORING

Designer parking tiles of ISI mark in covered area and pay inter locking tiles in open area

STAIR LANDING & ENTRANCE

Designer Tiles/Marble flooring with S.S. railing

WATER PROOFING SUNKEN SLAB TO TIOLET

Double coat of Teenoxy treatment

WATER PROOFING AND HEAT TREATMENT ON TOP ROOF

Water proofing of top slab by water proofing chemical and heat product treatment by backbat with chemical mixed plaster on top floor finishing.

OVERHEAD WATER TANK

Overhead water tank of adequate capacity.

BORING AND TUBE WELL

Boring & tube well of adequate capacity with adequate size ISI make submersible pump.

GENERATOR

- (a) Supply of 400 watt to each flat 8 common light lift 8 pump.
- (b) ISI mark silent Generator of adequate capacity.

LIFT

6 passenger capacity lift.

SECURITY & AUTOMATION

CCTV cameras at strategic point in the common area with digital video recorder.